



佑盛機械工業有限公司


YOW CHENG MACHINERY INDUSTRY CO., LTD

42942 台中市神岡區豐洲里東洲路 111 號

No. 111, Dong Zhou Rd., Shen Gang Dist., TAICHUNG, TAIWAN, R.O.C.

TEL: 886-4-25288637 252225326 FAX: 886-4-25288638

E-Mail: ycmtc@ms64.hinet.net Http: www.yowcheng.com.tw



SD-2T2 雙頭鑽孔機 DOUBLE END BORING M/C.(V&H)

SPECIFICATIONS :

型 式	MODEL	SD-2T2	SD-3T2
主軸馬力 (橫鑽)	Spindle motor(horizontal)	2HPx2	2HPx3
主軸馬力 (立鑽)	Spindle motor(vertical)	1HPx2	1HPx2
主軸速度	Spindle speed	60HZ-3500R.P.M	60HZ-3500R.P.M
直列鑽頭最大間距	Head in line max. distance between drills	2600 mm	2600 mm
直列鑽頭最小間距	Head in line min. distance between drills	280 mm	280 mm
並列鑽頭最大間距	Head at parallel max. distance between drills	2100 mm	2100 mm
並列鑽頭最小間距	Head at parallel min. distance between drills	300 mm	300 mm
最大鑽孔深度	Max. boring depth	80 mm	80 mm
立式座主軸行程	Vertical spindle travel	80 mm	80 mm
鑽孔深度	Vertical boring stroke travel	60 mm	60 mm
主軸行程 (橫鑽)	Horizontal spindle travel	100 mm	100 mm
夾持氣壓缸	Clamp cylinder	2	3
主軸距工作台最大距離	Max. spindle to table distance	60 mm	60 mm
壓力	Air Pressure (Horizonfal)	5.6 kg/c m ²	5.6 kg/c m ²
機械尺寸(mm)	Machine size	3100 x 750 x1600 mm	3100 x 1000 x1600 mm
裝箱尺寸(mm)	Packing size	3200 x 830 x1780 mm	3200 x 1080 x1780 mm
淨重/毛重	Net weight / Gross weight	800 kg / 1050 kg	930 kg / 1180 kg